

AIRSPEC® Double Stage Ring Blower

(SPAN Approved)



APPLICATIONS

- Air Drying
- Bubble Bath
- Oxygen Supply for Aquaculture
- Combustion Furnace
- Powder Conveyor
- Printing and packaging
- Aquarium
- OEM

FEATURES

- High Pressure
- Low Noise
- Low Vibration
- High Precision
- High Performance
- Compact

PERFORMANCE TABLE

Model	Power	Frequency	Voltage	Current	Pressure/ Vacuum	Air Flow	Noise Level	Weight	Inlet / Outlet
ARB	KW	HZ	V	A	mbar	M3/Min	dB	Kgs	
2529	2.2	50	208 / 440	7.8 / 4.5	375 / 280	2.6	66	28	PF 1 1/2"
2529	2.6	60	220 / 460	9.5 / 5.5	435 / 350	3.0	69	28	PF 1 1/2"
2629	4.0	50	208 / 440	14.3 / 8.2	460 / 355	3.7	74	45	PF 2"
2629	4.6	60	220 / 460	16.2 / 9.3	495 / 410	4.5	77	45	PF 2"
2729	5.5	50	208 / 440	21.0 / 12.0	515 / 410	5.2	75	72	PF 2"
2729	6.3	60	220 / 460	26.5 / 15.3	530 / 425	6.2	79	72	PF 2"
2829	7.5	50	400 / 720	27.0 / 15.6	320 / 320	9.6	76	112	PF 2 1/2"
2829	8.6	60	400 / 720	34.0 / 19.6	320 / 320	10.9	81	112	PF 2 1/2"
2919	11.0	50	400 / 720	46.8 / 27.0	600 / 430	9.6	76	142	PF 2 1/2"
2919	13.0	60	400 / 720	52.0 / 30.0	600 / 455	10.9	81	142	PF 2 1/2"
2929	16.0	50	400 / 720	65.0 / 37.5	600 / 430	9.6	76	160	PF 2 1/2"
2929	19.0	60	400 / 720	74.0 / 42.7	600 / 455	10.9	81	160	PF 2 1/2"

AIRSPEC® Turbo Blower



ATB Series

APPLICATIONS

- Wood Working Machine
- Drying Machine
- Hot Air Blower
- Plastic Extruder
- Textile Machine
- Film Making Machine

FEATURES

- Specially Designed for High Efficiency
- Longer Operation Life
- Low Vibration
- High Performance
- Meets Environmental Protection Requirement

PERFORMANCE TABLE

Model	Power	Frequency	Voltage	Current (Full Load)	Pressure	Air Flow (Max)	Outlet	Noise Level	Weight
ATB	KW	HZ	V	A	mbar	M3/Min	Inch	dB	Kgs
ATB-0400	0.4	50/60	208/440	2.1(1.2)	13.0/15.0	6/8	3"(Ø75)	57/70	18
ATB-0750	0.75	50/60	208/440	3.3(1.9)	18.5/26.5	15/18	4"(Ø100)	65/80	30
ATB-1500	1.5	50/60	208/440	6.5(3.8)	21.5/32.0	17/21	4"(Ø100)	74/90	40
ATB-2200	2.2	50/60	208/440	8.7(5)	28.5/38.0	33/38	5"(Ø125)	77/96	60
ATB-3700	3.7	50/60	208/440	14(8)	35.0/40.0	35/45	6"(Ø150)	80/100	74